

AP80 - Liquid Pro Glove

Collection: Aqua Gloves

Range: Hand Protection

Materials: Nylon, Elastic

Dipping:

Inner Pack: 12

Outer Carton: 216

Product information

Featuring the latest innovation in double coating technology, the Liquid Pro offers maximum liquid protection. The smooth latex is fully coated before a second latex foam palm dip is applied, this process ensures maximum and superior grip is achieved. An elasticated wrist provides for a secure fit.

Aqua Gloves

The ultimate barrier to water, liquids and non-aggressive substances. The Aqua range includes both highly water resistant and water proof gloves.

Hand Protection

A wide and increasing range of hand protection products is available. In order to help cater to every need. Only the best materials and manufacturing methods are used in the production of Portwests' extensive range of Hand Protection products....

Standards

AS/NZS 2161 .2

AS/NZS 2161 .3

EN ISO 21420: 2020 Dexterity 5

EN 388:2016 + A1:2018 (4131X)



Features

- Liquid Pro offers maximum liquid protection
- Latex foam coating for excellent grip in wet and dry conditions
- Dual latex coating for additional protection in tough conditions
- Seamless 13 gauge liner
- Lightweight and comfortable
- Elasticated cuffs for a secure fit
- Retail tag which aids presentation for retail sales
- Certified
- Latex dipped for maximum grip
- ANSI cut level A1



PRODUCT SPECIFICATION & TECHNICAL DATASHEET

AP80 - Liquid Pro Glove

Commodity Code: 6116930000

Test House

SATRA Technology Europe Ltd (Notified Body No.: NB: 2777)

Bracetown Business Park

D15 YN2P, Ireland

Cert No: 2777/25829-01/E00-00

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
AP80B4RS	Blue	65.0	40.0	50.0	0.0590	0.1300	5036108290628	25036108780857
AP80B4RM	Blue	65.0	40.0	50.0	0.0710	0.1300	5036108271863	25036108761726
AP80B4RL	Blue	65.0	40.0	50.0	0.0780	0.1300	5036108271856	25036108761719
AP80B4RXL	Blue	65.0	40.0	50.0	0.0830	0.1300	5036108271870	25036108761733
AP80B4RXXL	Blue	65.0	40.0	50.0	0.0910	0.1300	5036108290635	25036108780864